

okuma
INSPIRED FISHING



CONVECTOR

Low-Profile Line Counter

INSPIRED BY PRECISION

The Convector Low-Profile Line Counter features a compact graphite body and graphite side plates. The A6061-T6 machined aluminum, anodized spool will keep your braided or monofilament line tight and running straight. The exciting feature behind the Convector is the Quick Drop Switch technology. When engaged, this button will automatically engage the clutch as soon as you remove your thumb from the thumb bar.

The Convector Low Profile features a mechanical line counter function that measures in feet and utilizes Okuma's CVT- Clear View Technology anti-fogging system. The precision machine-cut brass main and pinion gears keep the reel running smooth along with three total stainless-steel ball bearings.

Available in both left and right hand retrieve, the Convector comes in at just 11.7 oz and utilizes a multi-disc carbonite drag system that puts out over 22 lbs of maximum drag pressure. The reel also features an On/Off clicker switch perfect for trolling applications.



CONVECTOR



Features

- Precision machine cut brass main and pinion gears
- Mechanical line counter function measures in feet
- CVT: Clear View Technology anti-fogging line counter
- 2BB + 1RB stainless steel bearings for long last performance
- Automatic trip, spool engagement mechanism
- A6061-T6 machined aluminum, anodized spool
- Multi-disc high output Carbonite drag system
- Dual anti-reverse for maximum reliability
- Synchronized levelwind optimized for braided line
- Quick Drop, switch for precision lure/bait placement
- On/Off clicker perfect for all trolling applications
- Rigid metal handle with TPE ergo grip knob
- Available in both right and left hand retrieve
- Convector LP Line Counter are backed by a 1-year limited warranty



QUICK DROP

Quick Drop Switch for accurate lure and bait placement.

STRIKE ZONE LINE COUNTER SYSTEM

Okuma's Strike Zone linecounter system incorporates a mechanical counter that precisely measures line based on spool revolutions. These counters measure in feet and are calibrated at the factory to be most accurate with a full spool and monofilament lines.



CVT SYSTEM

Okuma's CVT- Clear View Technology anti-fogging system.



QUICK DROP SYSTEM

The Convector Low-Profile Line Counter features a Quick Drop Switch function. When engaged, this button will automatically engage the clutch as soon as you remove your thumb from the thumb bar. This allows for precise and accurate placement of your bait or lure.



A6061-T6 MACHINED ALUMINUM, ANODIZED SPOOL

The A6061-T6 machined aluminum, anodized spool will keep your braided or monofilament line tight and running straight.

RIGID METAL HANDLE WITH TPE ERGO GRIP KNOB

The handle knob is designed with Ergo TPE material for anti-slip, ergonomic, and maximum comfort. It utilizes a metal handle arm for improved strength and reduced weight.



CONVECTOR

Model	Gear ratios	Bearings	Weight (g)	Line retrieve (cm)	Max Drag Pressure (kg)	Monofilament line capacity (diameter in mm.)	Frame	Sideplates	Spool
CV-354D	5.4:1	2BB+1RB	332	66	10	0.33/240, 0.37/180, 0.41/145	GR	GR	AL
CV-354DLX	5.4:1	2BB+1RB	332	66	10	0.33/240, 0.37/180, 0.41/145	GR	GR	AL

okuma
INSPIRED FISHING